



Earth Auger

EA08

SPECIFICATIONS

ITEM	U.S.A.	METRIC
CAPACITY	Up to 18 in. (46 cm) Dia. x 42 in. (107 cm) Long Auger	
PERFORMANCE	250 ft lb	339 Nm
FLOW RANGE	7 - 9 gpm	26 - 34 lpm
PRESSURE	up to 2000 psi	up to 138 bar
PORTS	-8 SAE O-Ring	
WEIGHT (less torque tube)	47 lbs	21 kg
HEIGHT (less auger)	11.7 in.	30 cm
WIDTH (across diagonal of handles)	46 in.	119 cm
CONNECTION	3/8 in. Flush-Face Quick Disconnect Coupler	
TORQUE TUBE EXTENSION RANGE	75 - 141 in.	190 - 358 cm
SPEED (at 8 gpm/30 lpm)	165 rpm	



EA08 shown with Torque Tube

Features and Benefits

The Stanley EA08 Earth Auger is powerful and lightweight featuring an output torque of 250 ft lb (339 Nm). The EA08 can handle a wide variety of earth boring applications. It comes standard with handles for two-man operation and a torque tube for easy one-man operation.

The telescoping torque tube can be attached to a trailer hitch or most any anchored object, for one-man operation. The torque tube may be attached 90 degrees to the side.

The ergonomically designed forward and reverse control valve lever is integrated into the handle. Unlike gasoline powered augers, the EA08's reverse control makes removing the auger from the hole nearly effortless.

The EA08 can be powered by many types of hydraulic power sources. Truck circuits, skid-steer loaders, backhoes and mini-excavators are just a few of the power sources that may be used.

A full line of earth augers are available. Drill diameters range

from 2 (8 cm) to 18 inches (35 cm) with lengths of 42 inches (91 cm). 15 inch (38 cm) extensions can be added for even more length.



Distributed by McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
 Tel.: 1-800-663-6344
 Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
 Tel.: 1-800-287-5714
 Fax: (905) 542-1335

ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
EA08101A	EA08101A	1-1/4 in. Square Female Snap Connection
EA08102A	EA08102A	1-3/8 in. Hex Male Pinned Connection

Torque Tube is included with above models.

ACCESSORIES

PART NO.	DESCRIPTION
39413	2 in. Trailer Ball / Bracket Anchor
43660	1-1/4 in. Hex Female Pinned Drive Connection
EA08101A - 1-1/4 in. Square Augers	
39409	8 in. Diameter x 42 in. OAL
39410	8 in. Diameter x 36 in. Full Flight Extension OAL
EA08102A - 1-3/8 in. Hex Augers and Accessories	
47406	2 in. Diameter x 42 in. OAL (Requires 58585 Coupler)
47407	3 in. Diameter x 42 in. OAL (Requires 58586 Coupler)
47408	4 in. Diameter x 42 in. OAL
47409	6 in. Diameter x 42 in. OAL
47410	8 in. Diameter x 42 in. OAL
47411	10 in. Diameter x 42 in. OAL
47412	12 in. Diameter x 42 in. OAL
47413	16 in. Diameter x 42 in. OAL
47414	18 in. Diameter x 42 in. OAL
47429	Digging Tooth with Hardface
47430	2 in. Center Screw Bit, 6-12 in.
47431	3 in. Center Screw Bit
47432	4 in. Center Screw Bit
58585	13/16 x 1-3/8 in. Hex Coupler for use with 47406 Auger
58586	1-1/8 x 1-3/8 in. Hex Coupler for use with 47407 Auger

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335

STANLEY

Distributed by
McCann Equipment Ltd.