



Ground Rod Driver

GD50



SPECIFICATIONS

ITEM	U.S.A.		METRIC
CAPACITY (GD50132RF)	1/2 and	5/8 in. Ro	12 and 16 mm Rod
CAPACITY (GD50133)	3/4 and	1 in. Ro	19 and 25 mm Rod
FLOW RANGE	5 - 9 gpm		19 - 34 lpm
PRESSURE	1500 - 2000 ps		105 - 140 bar
PORTS	-8 SA E Straight Thread O-Ring		
SYSTEM TYPE	Open Center/Closed Center		
WEIGHT	52 lbs		24 kg
LENGTH	25.5 in.		64.8 mm
CONNECTION	3/8 in. Flush-Face Quick Disconnect Couplers		
HOSE WHIPS	Yes		

GD50 shown minus hose whips, in-line valve and couplers

Features and Benefits

The Stanley GD50 Ground Rod Driver provides a competitive means of driving rods with proven, hard-hitting technology.

Two models are available, the GD50132RF that drives 1/2-inch and 5/8-inch rods the GD50133 that drives 3/4-inch and 1-inch rods.

The lifting eye allows the operator to suspend the driver above the rod with ease. The long side handles give the operator control during the driving process.

The in-line valve in the 8-foot hose whips gives the operator On/Off control where he is standing.

Both GD50 models have driving anvils which are designed to fit the rods which helps to minimize damage to the rod ends. The anvil which remains in contact with the rod while the hammer in the ground rod driver delivers its high-energy blows to the anvil. The deep socket of the anvil keeps the driver from jumping off the end of the rod.

The anvils are interchangeable, so that you can change the capacity of a ground rod driver by simply changing anvils. The removal of two bolts is all that is required to service the front end of the GD50.



Distributed by McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335

ORDERING INFORMATION

MODEL	P ARTNO.	DESCRIPTION
GD50	GD50132RF	Side Handle, 1/2 - 5/8 in. Rod
GD50	GD50133RF	Side Handle, 3/4 - 1 in. Rod

Note: Above models include two each hose whips with in-line valve, flush-face couplers and 8 ft hose whips.

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

STANLEY[®]

Distributed by
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335