



# Sinker Drill

## SK47

### SPECIFICATIONS



ITEM	U.S.A.	METRIC
CAPACITY	7/8 in. Hex x 4-1/4 in. Shank	
PERFORMANCE	2 in. x 10 ft. Deep Hole	
FLOW RANGE	7 - 9 gpm	26 - 34 lpm
PRESSURE	1500 - 2000 psi	105 - 140 bar
PORTS*	-8 SAE O-Ring (H), 3/8 in. NPT (A)	
WEIGHT	52 lbs	24 kg
LENGTH	23 in.	58 cm
WIDTH	14 in.	35 cm
CONNECTION	3/8 in. Male NPT Hose End	
HOSE WHIPS	Yes	
MOTOR	Integral	

\* (H) = Hydraulic  
(A) = Air

### Features and Benefits

The Stanley SK47 Sinker Drill is designed for utility construction, blast hole drilling, leak detection for gas utilities and dowel drilling.

The SK47 comes ready to use air flushing to clear holes of debris. The air flow automatically is shut off when the drill is Off.

The sinker drill features an easy start feathering trigger and a direct drive rotation motor for reliable service and fast and easy starting.

The rotation is independent of impact rate and is adjustable between 0 and 300 rpm. The sinker drill can drill up to a 2 in. (5 cm) diameter hole up to 10 ft (3 m) deep.

The SK47 is light and easy to handle. It is ideal for applications requiring frequent moves on the job site.

p/n 14538 12/01



Distributed by  
McCann Equipment Ltd.

**Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3**  
Tel.: 1-800-663-6344  
Fax: (514) 636-0365

**Toronto: 2178 Torquay Mews, Mississauga, On L5N 2M6**  
Tel.: 1-800-287-5714  
Fax: (905) 542-1335

## ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
SK47	SK47130	Air, Open Center System

## ACCESSORIES

PART NO.	DESCRIPTION
<b>CARBIDE ROCK BITS SHOULDER DESIGN FOR USE WITH AIR</b>	
05177	1-3/8 in. Diameter, Hex Thread
05178	1-1/2 in. Diameter, Hex Thread
<b>DRILL STEELS FOR USE WITH AIR</b>	
05171	1 in. Hex x 4-1/4 in., Hex Thread 48 in. U/C
05172	7/8 in. Hex x 4-1/4 in., Hex Thread 12 in. U/C
05174	7/8 in. Hex x 4-1/4 in., Hex Thread 24 in. U/C
05175	7/8 in. Hex x 4-1/4 in., Hex Thread 36 in. U/C
05176	7/8 in. Hex x 4-1/4 in. Hex Thread 48 in. U/C

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

**STANLEY**

Distributed by  
McCann Equipment Ltd.

**Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3**

**Tel.: 1-800-663-6344**

**Fax: (514) 636-0365**

**Toronto: 2178 Torquay Mews, Mississauga, On L5N 2M6**

**Tel.: 1-800-287-5714**

**Fax: (905) 542-1335**