



Chain Saw

CS05 - CS06



CS06

OPERATION AND PERFORMANCE

ITEM	CS05		CS06	
	U.S.A.	METRIC	U.S.A.	METRIC
Capacity (Cut Length)	12 & 15 in.	30 & 38 cm	12, 15, & 20 in.	30, 38, & 51 cm
Weight*	6.25 lb	2.8 kg	6.25 lb	2.8 kg
Length*	14 in.	36 cm	14 in.	36 cm
Width	9 in.	23 cm	9 in.	23cm
Pressure	1500-2000 psi	105-140 bar	1000-2000 psi	70-140 bar
Flow Range	4-6 gpm	15-23 lpm	7-9 gpm	26-34 lpm
Optimum Flow	5 gpm	19 lpm	8 gpm	30 lpm
Porting	-8 SAE 0-ring			
Connect Size & Type	3/8 in. NPT Male Adapter			
Hose Whips	No			
Motor	Integral			

* Without Bar

Features and Benefits

Stanley's hydraulic chain saws offer the highest power-to-weight ratio of any chain saw on the market today. They're ideal for bucket truck use because of their wide range of flow and pressure requirements.

Used around the world by utility companies, professional tree trimmers and construction crews. Safety has been designed in - all models feature interlocking triggers, hand guards, low kickback bars and chains. Hydraulic power doesn't require a flywheel to smooth power pulses so there is no chain coasting when you release the trigger.

Kickback is also reduced without the centrifugal force from the flywheel used on gas driven saws. Features a floating rim sprocket for longer wear and easy replacement.

Can be ordered in a wide variety of bar lengths. For extra flexibility, the "Dual Spool" models provide you with the ability to power the saws from either an open or closed-center hydraulic system using the same saw. Models can be special ordered for use with dedicated open or closed-center hydraulic systems.

The CS05/06 hydraulic, pistol-grip chain saws can be used for

all types of pruning and cleaning applications.

With an optimum input flow of only 5 gpm / 20 lpm, the CS05 is ideal for applications where the hydraulic power source is limited to 5 gpm / 20 lpm. (HTMA Type I)

The more powerful CS06 is designed for use on HTMA Type II circuits with a full 8 gpm / 30 lpm output.

Underwater models available - refer to ordering information.



Distributed by
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335

ACCESSORIES

PART NO.	DESCRIPTION
08348	Saw Chain, 12 in./30 cm Bar (.325 in. Pitch)
07641	Saw Chain, 15 in./38 cm Bar (.325 in. Pitch)
07642	Saw Chain, 20 in./51 cm Bar (.325 in. Pitch)
07935	File Guide with File - 21AP Chain (.325 in. Pitch)
08347	Saw Bar 12 in./30 cm (.325 in. Pitch)
07638	Saw Bar 15 in./38 cm (.325 in. Pitch)
07639	Saw Bar 20 in./51 cm (.325 in. Pitch)
07629	Rim Sprocket, 7-Tooth (.325 in. Pitch)
11464	Scrench (Comb. Screwdriver-Bar Nut Wrench)

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty does not apply if the maximum flow and pressure ratings are exceeded.

ORDERING INFORMATION

MODEL	PART NO.	SYSTEM	CAPACITY
CS0 5	CS0561 0	o.c./c.c	12 in./30 cm
	CS05620	o.c./c.c	15 in./38 cm
CS06	CS06610	o.c./c.c	12 in./30 cm
	CS06620	o.c./c.c.	15 in./38 cm
CS06	CS06610	o.c./c.c	12 in./30 cm
CS06 Railroad Model	CS06630S*	o.c./c.c	20 in./51 cm
	CS0661001*	o.c./c.c. CE	12 in./30 cm
	CS06630	o.c./c.c.	20 in./51 cm
	CS06920	o.c./c.c. , U/W	15 in./38 cm
	CS0692001*	o.c./c.c., CE, U/W	15 in./38 cm
	CS06	o.c./c.c. , U/W	20 in./51 cm

**Hose Whips and Couplers Included*

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

STANLEY

Distributed by
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335