



# Grinders

## GR30

### SPECIFICATIONS

| ITEM             | U.S.A.                           | METRIC     |
|------------------|----------------------------------|------------|
| CAPACITY         | 9 in. Wheel on 5/8-11 thrd arbor |            |
| SPEED            | 5600 rpm at 8 gpm (30 lpm)       |            |
| INPUT FLOW RANGE | 7-9 gpm                          | 26-34 lpm  |
| INPUT PRESSURE   | 1000-2000 psi                    | 70-140 bar |
| WEIGHT           | 12.5 lbs.                        | 5.7 kg     |
| LENGTH           | 8.5 in.                          | 21.6 cm    |
| WIDTH            | 8.7 in.                          | 22.1 cm    |
| HEIGHT           | 17.5 in.                         | 44.5 cm    |
| MOTOR            | Stanley Hyrevz™ Gear             |            |
| PORTING          | -8 SAE O-ring                    |            |
| HOSE WHIPS       | Yes, includes Speed Limiter      |            |



### Features and Benefits

**Stanley's GR30 Grinder** embodies the latest product improvements in this tool. The vertical grinder now has the Stanley Dual Spool Selector which allows the tool to be set for either open-center or closed-center systems. All the screw fasteners are stainless steel. The trigger spool is stainless steel. A trigger lock prevents accidental starting of the grinder.

**The integral Stanley Hyrevz™ gear motor** is manufactured to exacting standards to deliver maximum efficiency.

**The over-sized motor run-down valve** allows the motor to freely run down in speed when the grinder is turned off ensuring that a properly installed wheel will not spin off the spindle.

**The built-in reverse-check valve** in the handle prevents operating the grinder when reverse-plumbed to the hydraulic system. Preventing reverse operation ensures a long operating life for the hydraulic seals.

**The thick, tough layer of foamed-plastisol** covering the handle transmits very little heat. The foamed plastisol gives a more comfortable grip to the tool.

**The cast-in lifting eye** is always available, unlike screwed-in lifting rings which may come loose and fall off.

**The Stanley dual-spool selector** is accessible under a seal plug at the rear of the tool. Setting the tool for open- or closed-center operation is as simple as opening or closing a valve. The selector is not susceptible to moving under the vibration of use and is completely protected from acciden-

tal or unintentional access. The seal plug also protects the end of the trigger spool and dual-spool selector from water and dirt.

**There are two positions available** for the assist handle to be conveniently placed by the operator. Either position is at a most comfortable handling position from the valve handle.

**The wheel guard** is adjustable. By loosening the clamp screw which has an integral toggle handle, the guard may be rotated to any convenient position.

The grinders can be used with standard grinding wheels and brushes that are rated for at least 6500 rpm and have a hub with 5/8-11UNC straight thread.



Distributed by  
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3  
Tel.: 1-800-663-6344  
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6  
Tel.: 1-800-287-5714  
Fax: (905) 542-1335

## ORDERING INFORMATION

| ORDER NO. | DESCRIPTION                        |
|-----------|------------------------------------|
| GR30701   | 9-inch Grinder , oc/cc selector    |
| GR3070101 | 9-inch Grinder, oc/cc selector, CE |

All models include 3/8 HTMA flush faced quick couplers.

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

## ACCESSORIES

| PART NO. | DESCRIPTION   |
|----------|---|
| 02587    | Grinding wheel for Metal, 9-inch diameter x 5/8-11 thread   |
| 02588    | Grinding wheel for Masonry, 9-inch diameter x 5/8-11 thread |
| 03691    | Grinding wheel, 7-inch diameter x 5/8-11 thread             |
| 05194    | Adapter, 5/8-11 thread, depressed center wheel              |

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

**STANLEY**<sup>®</sup>

Distributed by  
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3  
Tel.: 1-800-663-6344  
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6  
Tel.: 1-800-287-5714  
Fax: (905) 542-1335