

STANLEY[®]Équipement
McCANN
Equipment Ltée/Ltd.**Impact Wrench****IW12**

IW12 Shown with flush face couplers. Couplers are not included on all models. See order information on back.

SPECIFICATIONS

ITEM	U.S.A.	METRIC
Chuck Type – Sq. Drive	3/4 in	1.9 cm
Weight	14 lb	6.4 kg
Length	9.5 in	24.1 cm
Width	4 in	10.2 cm
Hydraulic Pressure	1000-2000 psi	70-140 bar
Torque	250-1200 ft lb	340-1632 Nm
Flow Range	4-12 gpm	15-45 lpm
Optimum Flow	5-10 gpm	20-38 lpm
Porting	-8 SAE 0-ring	
Connect Size and Type	3/8 in Male Pipe Adapter	
Motor	Integral	

Stanley's hydraulic impact wrenches are used around the world by electric and gas utilities, construction crews, municipal agencies, and railroad crews.

No other tool, whether air or electric driven, can match the power, light weight and overall efficiency of our impact wrenches.

The IW12 can handle a wide variety of applications. The IW12 impact wrench features adjustable impact intensity.

The rugged impact wrench mechanism is simple to maintain and has many features to give it proven reliability. Torque transmission to the operator is minimal with the swing hammer design.

Designed to run from a wide range of hydraulic circuits, the IW12 is used for nut, bolt and anchor bolt driving and is equally popular for wood boring and drilling.

The larger feathering trigger is convenient to use and gives the operator complete control of the wrench. The standard reversing valve provides instant reverse.

For operator comfort the IW12 handle is coated with a heat insulating, shock absorbing material.

**Underwater models available.
Refer to ordering information.**

STANLEY[®]

Distributed by
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335

ORDERING INFORMATION

ORDER NO.	DESCRIPTION
IW12140	Impact Wrench, 3/4 in. sq. Drive
IW12140S	Impact Wrench, 3/4 in. sq. Drive, with HTMA* Flush Face Couplers
IW1214001	Impact Wrench, 3/4 in. sq. Drive, with Flush Face Couplers, CE
IW12340C	Impact Wrench, 3/4 in. sq. Drive, U/W
IW1234001	Impact Wrench, 3/4 in. sq. Drive, U/W, CE

*Meets Specifications as Required by The Hydraulic Tool Manufacturer's Association (HTMA)

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ACCESSORIES

PART NO.	DESCRIPTION
01857	Adjustable Chuck & Adapter – 3/4 in sq female x 3/4 in Chuck
05080	Adapter – 5/8 in hex x 1/2 in sq male
06790	Adapter – 3/4 in sq anvil to 5/8 in hex
Sockets	Please refer to specification sheet 30997, Impact Wrench Sockets for IW12 / IW16, for available sockets and additional accessories.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

STANLEY[®]

Distributed by
McCann Equipment Ltd.

Montreal: 10255 Cote De Liesse, Dorval, QC H9P 1A3
Tel.: 1-800-663-6344
Fax: (514) 636-0365

Toronto: 2178 Torquay Mews, Mississauga, ON L5N 2M6
Tel.: 1-800-287-5714
Fax: (905) 542-1335